LED | **IP40** | **220~240 VAC** | **RoHS** | CE

ES-BS4

☐ White

PARAMETER

Model	ES-BS4
Power	4W
Battery	Ni-Cd (3.6V 900mAh)
Charge	Auto
Full charge time	24 hours
Hours	3 hours
Function	Switch off circuit when fully charged
Installation	Ceiling cladding (2 sides), can change the length of hanging wire

ALTERNATIVES

S1 LỐI THOÁT EXIT →

S2 ← LỐI THOÁT EXIT

S3 LỐI THOÁT EXIT ↑

S4 ↓ LỐI THOÁT EXIT

S5 ← EXIT LỐI THOÁT →

S6 → EXIT LỐI THOÁT ←

S7 WC

S8 EXIT LỐI THOÁT

INSTALLATION INSTRUCTIONS

1. Remove the mounting plate

LỐI THOÁT EXIT →
Battery Driver

2. Fix base plate on the celling by screw

Battery Driver

3. Connect the main line to the power wire of the lamp

≅ AC 220V
Battery Driver

LỐI THOÁT EXIT →

4. Install finishing

Test button
adjust the wire length

LỐI THOÁT EXIT →

PACKING

LỐI THOÁT EXIT →

1 pcs

VinaLED®
Dẫn đầu về độ sáng và chất lượng

235mm
65mm
340mm